



CLOUD



AC1200



PoE



EASY

Product Overview

IgniteNet™'s SunSpot™ AC is the most cost-effective, cloud-managed 802.11ac access point on the market. The SunSpot™ AC contains 2 independent, concurrent operation radios - one 802.11ac (5GHz) radio and one 802.11n (2.4GHz) radio - capable of delivering blisteringly fast wireless speeds. The sleek design of the SunSpot™ AC allows it to be placed inconspicuously in both offices and homes, bringing fast wireless connections to hard-to-reach locations.

Key Features and Benefits

Cloud-Enabled Networking

The IgniteNet™ SunSpot™ AC is cloud-enabled out of the box allowing for easy, highly scalable installation, configuration, and management.

Dual Band AC1200 Operation

The SunSpot™ AC is capable of operating simultaneously at 2.4GHz (802.11b/g/n) as well as 5GHz (802.11a/n/ac) to supply ample throughput for the most demanding applications.


Powerful, Flexible Configuration

The SunSpot™ AC can operate either as a stand-alone access point or as a coordinated, cloud-managed access point, easily meeting the requirements of any installation.

Robust Yet Simple Mounting Options

The SunSpot™ AC can be wall, ceiling, or desktop mounted, greatly simplifying installations in both offices and homes.

Product Variants



SS-AC1200



SS-N300



I/O Region (all models)

Features

HARDWARE FEATURES

- ✓ 1x Gigabit Ethernet Port (PoE IN)
- ✓ 2x 10/100 Fast Ethernet Ports
- ✓ 1x USB 2.0 Port
- ✓ Dual flash image support

LEDs

- ✓ Power, Ethernet, Wireless, Health/Status, Controller Status

DIMENSIONS (L x W x H)

- ✓ 200 x 200 x 50 mm

WEIGHT

- ✓ 626 g

POWER

- ✓ 12V/2A DC
- ✓ 802.3at Power over Ethernet

OPERATING ENVIRONMENT

- ✓ Operating Temperature: 0C° to +50C°
- ✓ Store Temperature: -40C° to 70C°
- ✓ Operating Humidity: 10 to 90% non-condensing (RH)

REGULATORY / STANDARDS COMPLIANCE

- ✓ FCC/IC
- ✓ CE

RF PERFORMANCE (TX)

- ✓ 2.4GHz:
 - 30dBm @ 6Mbps, 27dBm @ 300Mbps
- ✓ 5GHz:
 - 28dBm @ 6Mbps, 24dBm @ 866Mbps

KEY FEATURES

- ✓ Supports Service Provider and Enterprise type networks
- ✓ Stand-alone or Cloud-controlled operating modes
- ✓ AP/Client/Client WDS modes with Flexible Bridging and Routing
- ✓ 802.11 a/b/g/n/ac, 2x2, Dual Band Dual Concurrent (2.4GHz and 5GHz)
- ✓ Supports up to 8 SSIDs per radio
- ✓ Optional single band available
- ✓ IEEE802.11e Wi-Fi Multimedia (WMM-QoS)
- ✓ WEP (64/128-bit), WPA,WPA2-PSK,WPA2-AES, PSK and Enterprise
- ✓ Admission control by client MAC address

APPLICATIONS

- ✓ Enterprise AP
- ✓ 3G/4G Offload
- ✓ Managed WiFi Services

Ordering Information

Part Number	Description
SS-AC1200-XX	SunSpot™ AC1200 - Dualband Concurrent Enterprise AP w/ integrated
SS-N300-XX	SunSpot™ N300 - Single Band Enterprise AP w/ integrated antennas

****XX is used to denote localization (US, EU, UK, AU, CN, JP)**

Contact