

# ES3510MA-AC/DC

## L2 Fast Ethernet Standalone Switch



### Product Overview

The Edgecore ES3510MA-AC/DC is a high-performance Fast Ethernet Layer 2/4 switch featuring 10 ports; 8 10/100 Mbps ports and 2 combination Gigabit Ethernet RJ-45/SFP (Small Form Factor Pluggable, dual-speed 100/1000 Mbps) ports. It is ideal for Fast Ethernet desktop connectivity and wiring closet installations. Using IP Clustering in a virtual stack of up to 36 switches, the whole stack can be managed as a single entity with a single IP address. This switch is packed with features and is a cost-effective solution that brings continuous availability, enhanced security, and advanced QoS to the network edge, while maintaining simplicity of management.

### Key Features and Benefits

#### Performance and Scalability

This entry-level managed switch provides 5.6 Gbps wire-speed switching performance across all ports. This enables the switch to fully support existing high-performance PCs and laptops, which significantly improves application response times and the speed of large file transfers.

The two Gigabit Ethernet combination ports enable uplink flexibility, offering copper or fiber uplinks to servers or the network backbone.

#### Continuous Availability

IEEE 802.1w Rapid Spanning Tree Protocol support provides loop-free and redundant links to the core network with rapid convergence, which ensures a faster recovery from failed links and enhances overall network stability and reliability.

The IEEE 802.1s Multiple Spanning Tree Protocol runs STP per VLAN base (up to 32 instances), providing Layer 2 load sharing on redundant links.

Multicast VLAN Registration (MVR) is designed for applications such as Media-on-Demand that stream multicast traffic across an Ethernet network. IGMP snooping prevents the flooding of IP multicast traffic and limits bandwidth-intensive video traffic to only ports connected to subscribers.

The voice VLAN feature enables access ports to carry IP voice traffic from IP phones.

IEEE 802.1Q Tunneling (Q-in-Q) is designed for service providers carrying traffic for multiple customers across their networks.

#### Comprehensive QoS

Traffic is prioritized according to 802.1p, DSCP, IP precedence, and TCP/UDP port number, giving optimal performance to real-time applications such as voice and video.

Asymmetric bidirectional rate-limiting, per-port or per-traffic class, preserves network bandwidth and allows maximum control of network resources.

#### Enhanced Security

Port Security limits the total number of devices that can access a switch port based on MAC address, and protects against MAC flooding attacks.

IEEE 802.1X port-based or MAC-based access control ensures all users are authorized before being granted access to the network. User authentication is carried out using a standard-based RADIUS server and supports dynamic VLAN assignment and a guest VLAN.

Access Control Lists (ACLs) can be used to restrict access to sensitive network resources by denying packets based on source and destination MAC addresses, IP addresses, and TCP/UDP ports. ACLs are hardware supported, so switching performance is not compromised.

Secure Shell (SSH v1.5/v2.0) and Secure Sockets Layer (SSL/HTTPS) encrypts Telnet and web access to the switch, providing secure network management.

TACACS+ 3.0 Authentication for applications such as network access or IP mobility enables centralized control of the switch and prevents unauthorized users from altering switch configuration.

Private VLANs isolate edge ports to ensure user privacy.

#### Simple Management

An industry-standard Command Line Interface (CLI), accessed through the console port or Telnet, provides a convenient way to configure and troubleshoot the switch.

IP Source Guard can be enabled with DHCP snooping on trunk ports with a large number of VLANs to filter and control IP traffic access to the network.

DHCP snooping provides security by filtering un-trusted DHCP messages and by building and maintaining a DHCP snooping binding table.

DHCP Option 82 is feature that adds device information to client TCP/IP configuration requests that are relayed to a DHCP server.

## Features

### Physical Ports

- 8 10/100BASE-TX ports
- 2 Combination Gigabit (RJ-45/SFP) ports
- (SFP ports support dual-speed 100BASE-FX/BX and 1000BASE-SX/LX/LHX)
- 1 RS-232 RJ-45 console port

### Performance

- Switching Capability: 5.6 Gbps
- Packet Buffer Size: 4 MBit
- MAC Address Table: 8K
- Forwarding Rate : 4.1 Mpps

### L2 Features

- Auto-negotiation for port speed and duplex mode
- Flow Control:
  - IEEE 802.3x for full-duplex mode
  - Back-Pressure for half-duplex mode
- Spanning Tree Protocol:
  - IEEE 802.1D Spanning Tree Protocol (STP)
  - IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
  - IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- Spanning Tree Fast Forwarding
- Loopback Detection
- Auto Edge Port
- BPDU Filter
- BPDU Guard
- Root Guard
- VLANs:
  - Supports 4093 IEEE 802.1Q VLANs
  - Port-based VLANs
  - MAC-based VLANs
  - IP-Based
  - IEEE 802.1v protocol-based VLANs
  - Private VLANs
  - Selective Q-in-Q
  - GVRP
  - Q-in-Q
  - Voice VLANs
- Link Aggregation:
  - Static Trunk
  - IEEE 802.3ad Link Aggregation Control Protocol
  - Unicast/Multicast traffic
- Balance over Trunking port
- IGMP Snooping:
  - IGMP Snooping v1/v2
  - IGMP v1/v2 querier
  - IGMP Immediate Leave
  - IGMP Filtering
  - IGMP Throttling
  - IGMP SNP Leave Proxy
  - IGMP v1/v2/v3 Proxy
- Storm Control: Broadcast/Multicast/UnknownUnicast
- MVR (Multicast VLAN Registration)
- Supports jumbo frames up to 10 KB
- G.8032 (ERPS)
- Digital Diagnostic Monitoring (DDM)

### QoS Features

- Priority Queues: 4 hardware queues per port
- 802.1p-based CoS
- IP DSCP-based CoS
- TCP/UDP port-based CoS
- WRR priority scheduling
- Strict priority scheduling
- Hybrid scheduling
- Rate Limiting (ingress and egress, per port base)
  - FE: Resolution 64 Kbps ~ 100 Mbps
  - GE: Resolution 64 Kbps ~ 1000 Mbps
- Diffserv

### IPv6 Features

- IPv4/IPv6 dual protocol stack
- IPv6 address type
  - Unicast
  - Multicast (internal used)
- ICMPv6
- ICMPv6 Redirect (Host)
- IPv6 Path MTU Discovery
- IPv6 Neighbor Discovery
  - Router discovery
  - Duplicate Address Detection
  - Parameter discovery
  - Prefix discovery
  - Address resolution
  - Unreachable neighbor detection
- Stateless autoconfiguration
- Manual configuration
- SNMP over IPv6
- HTTP over IPv6
- SSH over IPv6
- IPv6 Telnet support
- IPv6 DNS resolver
- IPv6 Syslog support
- IPv6 SNTP support
- IPv6 TFTP support
- Remote IPv6 Ping
- Ping over IPv6
- Trace route over IPv6
- IPv6 sFlow
- DHCPv6
  - Client
  - Snooping
- MVR6
- IPv6 Source Guard
- RA Guard
- MLD Snooping v1/v2
- IPv6 ACL

## Features

### Management

- Switch Management:
  - Web-based management
  - CLI-based management
- Telnet
  - Client
  - Server
- Software/configuration download/upgrade
  - TFTP
  - HTTP
  - FTP
- Dual Images
- Auto Upgrade
  - TFTP
  - FTP
- SNMP
  - v1
  - v2c
  - v3
- RMON
  - RMON1 (groups 1, 2, 3, and 9)
- BOOTP
  - Client
- DHCP
  - Client
  - Snooping
  - Snooping Option82
  - Dynamic Provision (via Option 66, 67)
- IP Source Guard
- Port mirroring
- VLAN mirror
- MAC-based mirror
- Remote port mirror (RSPAN)
- Event/Error Logging
  - Syslog (local flash)
  - Remote log
  - SMTP (e-mail notification)
- DNS
  - Client
  - Proxy
- Remote Ping
- SNTP
- NTP
- IP Clustering
- LLDP (802.1ab)
  - Link Layer Discovery Protocol (LLDP)
  - LLDP-MED (VoIP related)
- Mac flush
- Dynamic ARP Inspection (DAI)
- Auto Traffic Control (ATC) (SW rate limit)
- Delay reload
- Cable diagnostics/TDR

### OAM (Operations Administration Maintenance)

- IEEE 802.3ah Link Ethernet Link OAM
- IEEE 802.1ag Connectivity Fault Management
  - Connectivity check
  - Lookback
  - Linktrace
- ITU-T Y.1731 Performance and Throughput Management
  - Frame Delay
  - Frame Delay variation

### Security

- Port security
- IEEE 802.1X:
  - Port-based
  - MAC-based
  - VLAN assignment QoS assignment
  - Guest VLAN
  - Supplicant support
  - EAPOL frames pass-through
- MAC authentication
- WEB authentication
- RADIUS authentication
- RADIUS accounting
- TACACS+ authentication
- TACACS+ authorization
- TACAXS+ accounting
- Access Control List:
  - L2/L3/L4
  - Time-based
- SSH (v1.5/v2.0)
- HTTPS/SSL
- User name password authentication:
  - Local authentication
  - Remote authentication
- Intrusion Lock (Link Detection)
- MAC filter
- Traffic Segmentation
- PPPoE Intermediate Agent

### Mechanical

- Dimensions (W x D x H): 19.5 cm x 11.5 cm x 3.6 cm (small form factor)
- Weight: 0.68 kg (1.5 lb)
- LED Indicators: Port, Uplink, System, Diagnostic

### Safety

- UL (CSA 22.2. NO 60950-1 & UL60950-1)
- CB (IEC60950-1)

### Electromagnetic Compatibility

- CE Mark
- FCC Class A
- CISPR Class A

### Environmental Specifications

- Temperature:
  - IEC 68-2-14
  - 0°C to 45°C (Standard Operating)
  - 40°C to 70°C (Non-Operating)
- Humidity: 10% to 90% (Non-condensing)
- Vibration: IEC 68-2-36, IEC 68-2-6
- Shock: IEC 68-2-29
- Drop: IEC 68-2-32

### Power Supply

- DC Power Input: 36 to 75 VDC, 0.373 A
- Power Supply Connector: 48 VDC supply circuit
- Power Consumption: 32 Watts maximum

## Features

### Warranty

Please check [www.edge-core.com](http://www.edge-core.com) for the warranty terms in your country.

### For More Information

To find out more about Edgecore Networks Corporation products and solutions, visit [www.edge-core.com](http://www.edge-core.com).

### About Edgecore Networks Corporation

Edgecore Networks Corporation is in the business of providing innovative network solutions. In the service provider network, in the data center or in the cloud, Edgecore Networks Corporation delivers the software and systems that transform the way the world connects. Edgecore Networks Corporation serves customers and partners worldwide. Additional information can be found at [www.edge-core.com](http://www.edge-core.com).

Edgecore Networks Corporation is a subsidiary of Accton Technology Corporation, the leading network ODM company. The Edgecore Data Center switches are developed and manufactured by Accton.

To purchase Edgecore Networks solutions, please contact your Edgecore Networks Corporation representatives at +886 3 563 8888 (HQ) or +1 (949)-336-6801 or authorized resellers.

© Copyright 2016 Edgecore Networks Corporation. The information contained herein is subject to change without notice. This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered by Edgecore Networks Corporation. Edgecore Networks Corporation shall not be liable for technical or editorial errors or omissions contained herein.

## Ordering Information

Optional Accessories	Product Description
ET4201-SX	1Gbps, Small Form Factor Pluggable (Distance: 500 m; Wavelength: 850nm)
ET4201-LX	1Gbps, Small Form Factor Pluggable (Distance: 10 km; Wavelength: 1310 nm)
ET4201-LHX	1Gbps, Small Form Factor Pluggable (Distance: 40 km; Wavelength: 1310 nm)
ET4202-SX	1Gbps, Small Form Factor Pluggable (Distance: 550 m; Wavelength: 850 nm, DDM)
ET4202-LX	1Gbps, Small Form Factor Pluggable (Distance: 10 km; Wavelength: 1310nm, DDM)
ECView Pro	Network Management Software