

ZYXEL



NAP102

802.11ac Dual-Radio Nebula Cloud Managed Access Point

The Zyxel Nebula NAP102 802.11ac Dual-Radio Nebula Cloud Managed Access Point is a high-performance, cloud-managed 2x2 MIMO 802.11ac AP designed for deployments in offices, schools, hospitals, hotels and retail stores. With ultra-fast speeds of up to 1.2 Gbps, the Nebula NAP102 has revolutionized cloud managed wireless networking to a higher entry level. Featuring dual-concurrent, dual-band operation and advanced technologies such as Dynamic Channel Selection, Load Balancing and Smart Client Steering, the NAP102 delivers high throughput and reliable coverage for a superb Wi-Fi experience.

Every Nebula AP has been engineered for cloud management. Based on the NETCONF standard, all data traffics between the cloud and access points are exchanged using secure transports to ensure transaction-safe configuration on all Nebula devices. Furthermore, with the intuitive management interface, administrators are able to manage all the access points quickly even without training.

Benefits

Zero-touch deployments

The Zyxel Nebula NAP102 auto-configures itself after installation and then automatically connects to the Nebula cloud to join the network; so auto-configuration, provision, monitoring and diagnostics can be performed anytime, anywhere. This simplifies network setup and enables deployment of Nebula APs to a remotely located network even by non-IT professionals.



Cloud-managed, dual-radio 2x2 MIMO 802.11ac access point



Supports combined data rates of up to 1200 Mbps



Self-configuration and zero-touch deployment



Enterprise-class security and RF optimization



Dynamic Channel Selection, Load Balancing and Smart Client Steering



nebula

Optimized wireless experience

The Zyxel Nebula NAP102 delivers optimized wireless experience for users with comprehensive wireless features such as Dynamic Channel Selection (DCS), Load Balancing, and Smart Client Steering, etc. DCS avoids interference from co-channeling and overlapping channels continuously, while Load Balancing and Smart Client Steering which features Band Select and Balance for more spectrum to provide more stable, reliable wireless connections.

Smoke detector design that blends into environments

Different from traditional business access points, the Zyxel Nebula NAP102 comes in a "smoke detector" ceiling-mount design. Since the "smoke detector" design is not invasive, there is no need to hide it behind the ceiling tiles; and the ceiling-mount optimized RF design can provide its best performance and coverage. In addition, the NAP102 is plenum-rated and made of non-toxic materials without hazardous emission – critical for public indoor wireless deployments.

Enterprise-class security

The Zyxel Nebula NAP102 inherits the NETCONF protocol for secure configuration changes. In terms of authentication and data encryption, it supports WPA2 enterprise protection and a wide range of Extensible Authentication Protocol (EAP) types, including EAP SIM for smartphones. Besides, the NAP102 also features access control and Layer-2 isolation for privacy protection. The comprehensive security features ensure NAP102 to deliver enterprise-grade protection to the entire network.

Ultra-fast speed

The Zyxel Nebula NAP102 is a 2x2 802.11ac AP that provides Gigabit Wi-Fi experience. The concurrent dual-band support meets the pervasive BYOD demands to support more clients with equal signal coverage in both 2.4 GHz and 5 GHz bands.




Real-time control of all the devices through a single pane of glass



Monitor AP usage and client report by different time intervals and view historical status record via the intuitive management interface

Applications Diagram



Nebula cloud management architecture



Robust Hardware

Advanced antenna design


NAP102 antenna module provides better coverage in TX/RX and eliminates dead spots with same output power by using reflector to optimize pattern for better coverage.



Solid capacitor for longevity

All-solid capacitor design provides up to 6 times lifespan than electrolytic capacitors that delivers better stability and reliability.

Specifications

Model		NAP102
Product name		802.11ac Dual-Radio Nebula Cloud Managed Access Point
		
RF Specifications		
Frequency band		2.4 GHz (IEEE 802.11 b/g/n) <ul style="list-style-type: none"> • USA (FCC): 2.412 to 2.462 GHz • Europe (ETSI): 2.412 to 2.472 GHz • Taiwan (TW): 2.412 to 2.462 GHz 5 GHz (IEEE 802.11 a/n/ac) <ul style="list-style-type: none"> • USA (FCC): 5.15 to 5.35 GHz; 5.725 to 5.850 GHz • Europe (ETSI): 5.15 to 5.35 GHz; 5.470 to 5.725 GHz • Taiwan (TW): 5.15 to 5.35 GHz; 5.725 to 5.850 GHz
802.11n/ac premium features		<ul style="list-style-type: none"> • 2x2 Multiple-Input Multiple-Output (MIMO) with two spatial streams • Maximal Ratio Combining (MRC) • 20-, 40- and 80-Mhz channels • Packet aggregation: A-MPDU (Tx/Rx), A-MSDU (Tx/Rx) • Cyclic Delay Diversity (CSD) support • Maximum Likelihood Demodulation (MLD) support • Low Density Parity Check (LDPC) support
Conducted typical transmit output power (dBm)	FCC 11b/g	23
	FCC 11g/n	23
	FCC 11a	26
	FCC 11n/a (ac)	26
	EU 11b/g	20
	EU 11g/n	20
	EU 11a	26
	EU 11n/a (ac)	26
Antenna system		Embedded internal antenna
Antenna gain		2.4 GHz 3 dBi; 5 GHz 4 dBi
Support data rate		<ul style="list-style-type: none"> • 802.11 a/g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps • 802.11n: up to 300 Mbps in MCS15 (40 MHz; GI = 400 ns) • 802.11ac: up to 866 Mbps in MCS9 (80 MHz; 2 spatial streams; GI = 400 ns)
Receive sensitivity		Min. Rx sensitivity up to to -99 dBm
Interfaces		
Number of 10/100/1000M LAN		1
Console port		4-Pin serial
PoE		Yes
PoE power draw		9 W
Wireless Security		
WEP		Yes
WPA/WPA2-PSK		Yes
WPA/WPA2-Enterprise		Yes
WLAN access control list		Yes
EAP types		TLS, TTLS, PEAP, FAST, AKA and SIM
IEEE 802.1X		Yes
Number of SSID		8 (per radio)
MAC filtering		Yes

Wireless Security		
Layer-2 isolation		Yes
RADIUS authentication		Yes
Captive portal		Yes
Network		
VLANs		Yes
DHCP client		Yes
QoS (PG)		
WMM		Yes
WMM power save		Yes
DiffServ marking		Yes
Management		
Cloud managed		Yes
ZON utility		Support
Smart connect		Neighbor device discovery
Others		
Plenum rating		Yes
Input power		12 VDC, 1 A
MTBF (hr)		1,241,824
Standard Compliance		
Ethernet		IEEE 802.3, IEEE 802.3u
PoE		IEEE 802.3af
WLAN		<ul style="list-style-type: none"> • 802.11b: DBPSK, DQPSK, CCK • 802.11g: BPSK, QPSK, 16-QAM, 64-QAM • 802.11a: BPSK, QPSK, 16-QAM, 64-QAM • 802.11n: BPSK, QPSK, 16-QAM, 64-QAM • 802.11ac: BPSK, QPSK, 64-QAM, 256-QAM
Certifications		
Radio		ETSI EN 300 328 V1.71: 11-2006, EN 301 893 V1.5.1 FCC Part 15.247, FCC Part 15E, LP0002, EN 60601-1-2: 2007
EMC		EN 301 489-1 V1.8.1: 11-2008, EN 301 489-17 V2.1.1: 05-2009 EN55022: 2010, EN55024: 2010, EN61000-3-2/-3 FCC Part 15.107, BSMI CNS13438.99, CNS14336: 99
Safety		EN 60950-1: 2006 + A11: 2009 + A1: 2010 + A12: 2011, IEC 60950-1: 2005; BSMI
Physical Specifications		
Item	Dimensions (WxDxH)(mm/in.)	130 x 130 x 54.7/5.12 x 5.12 x 2.17
	Weight (g/lb.)	300/0.67
Packing	Dimensions (WxDxH)(mm/in.)	278 x 209 x 72/10.94 x 8.23 x 2.83
	Weight (g/lb.)	700/1.54
Included accessories		<ul style="list-style-type: none"> • Power adapter • Wall/Ceiling-mount plate
Environmental Specifications		
Operating	Temperature	0°C to 50°C/32°F to 122°F
	Humidity	10% to 90% (non-condensing)
Storage	Temperature	-30°C to 70°C/-22°F to 158°F
	Humidity	10% to 90%

Weather-Proof Mounting Option

Outdoor Enclosure

People like to enjoy the combination of great view, fresh air and Wi-Fi service when they're outdoors. This weather-resistant enclosure brings the Zyxel indoor AP outdoors to make deployments in places such as parks, campus, poolside or camping yard convenient and affordable. This enclosure allows the AP to be easily mounted on any wall or pole. The durable enclosure is designed to withstand a wide range of temperature from 50°C to -20°C, waterproof the APs with IPX5 rating certified and extend lifespan with the UV stabilized plastic, which makes it the most reliable weatherproof enclosure.

Features

- **Compatible with various APs** including unified, cloud-managed and standalone units
- **Wide operating temperature** range from 50°C to -20°C
- **Compact size** easily blends into any environment seamlessly
- **UV stabilized plastic** extends enclosure lifetime
- **Flexible mount design** for wall mount, or pole mount installation with pole mount kit (sold separately)
- **IPX5 rating** makes Zyxel indoor AP weatherproof



Wall mount installation



Pole mount installation

Specifications

Model	Enclosure
Dimensions (WxDxH)(mm/in.)	238.54 x 249.72 x 86.97/9.39 x 9.83 x 3.42
Weight (kg/lb.)	0.64/1.4
Mounting options	Wall, Pole (pole mount kit is sold separately)
Certified	IPX5
Adjustability	Swivel +/-40° Tilt +/-15°

Compatibility List

Model	
	<ul style="list-style-type: none">• NWA1123-ACv2• NWA5121-N• NWA5121-NI• NWA5123-AC• NAP102
	<ul style="list-style-type: none">• NWA1123-AC PRO• WAC6103D-I• NAP203



For more product information, visit us on the web at www.zyxel.com

Copyright © 2017 Zyxel Communications Corp. All rights reserved. Zyxel, Zyxel logo are registered trademarks of Zyxel Communications Corp. All other brands, product names, or trademarks mentioned are the property of their respective owners. All specifications are subject to change without notice.

Datasheet **NAP102**



5-100-02617006 05/17